



## MECANIQUE ET ENGRENAGE MODERNES

Service administratif et comptable

15 av. Barthélémy Thimonnier - BP 25

69641-CALUIRE CEDEX - France

Tel : 00 33 (0)4 78 23 98 54

Fax : 00 33 (0)4 78 23 07 17

Siège social et usine

Z.I Le minaret

24450 - LA COQUILLE

Tel : 00 33 (0)5 53 52 85 48

Fax : 00 33 (0)5 53 52 05 84

# BAND SAW MILL



## Standard band saw mill for softwood and hardwood :

- ◆ Log transfer chain pitch 150mm , carrying capacity: 30 tons
- ◆ Lifting log chain 4 arms length 2m pitch 38.1mm with pneumatic loading cams
- ◆ Log carriage type DGR 4 headblocks, 2 Ø100mm chromed round slide, pneumatic dog opening , hydraulic dog overlapping 20 to 230 mm, microprocessor networks with a touch screen interface, headblocks are move by a variable speed motor, pneumatic slab turner and chain log turner.
- ◆ Slabber moves on 2 chromed round slide with hydraulic servo-cylinder
- ◆ 63'' band saw headrig, hydraulic tensioning of the blade, top saw guide can raise and fall , electric motor and starter :125 HP.
- ◆ **Option :** Moving saw detection and automatic lubricator of blade.

Site Internet : <http://www.memwood.com> - E-mail : [contact@membois.fr](mailto:contact@membois.fr)

# BAND SAW MILL



Headrig, carriage and conveying equipment  
Hydraulic tensioning of the blade  
Lifting top saw guide  
Infeed live roller for double cut  
Motorised roller included in the headrig



Ergonomic seated control desk.  
Air conditioned cabin with tilted front glass  
Microprocessor networks with a touch screen interface



Hydraulic shifting dogs 20 to 230mm for skewing the log after dogging.

